HEATED SELF-SERVICE DISPLAY SPECIFICATIONS el : V 100 LS 5 PULSE Manufacturer :

Model: V100 LS 5 PULSE



PERFORMANCE

5 stainless steel heated levels including 4 presentation shelves. Individual LED lighting

Regulated and ventilated shelves thanks to 'FORCED AIR' technology to keep products warm and packed at legal temperature

Our hot display cases are approved and guarantee that foodstuffs are kept at 145°F temperature at heart

The unit is maintained at the legal temperature by a curtain of hot air in the front. Regulation by thermostat (front display facing customers).


Quartz lighting and tempered glass protection.


ERGONOMIC

Side windows for panoramic view and tempered glass retaining stop on shelves 4 casters including 2 with brakes.

OPTIONS

- Front glass door for the protection of the enclosure warm against drafts







SAFETY

Tempered glass protection.

POWER SUPPLY

- Standard: 220V TriPhase
- 20 Amps
- 4200 Watts









405 N. Oak Street, Inglewood CA 90302 Toll free (888) 671 0630 - Tel. (310) 671 0345 - Fax (310) 680 2879

E-mail: info@1515design.com Website: www.1515design.com



HEATED SELF-SERVICE DISPLAY SPECIFICATIONS el : V 100 LS 5 PULSE Manufacturer :

Model: V100 LS 5 PULSE



FRONT VIEW SIDE VIEW 39 5/16" 33 1/8"

Crated Weight: 589 lbs.

References	Width	Depth	Height	Voltage	Plug	Power
V 100 LS 5 PULSE	39 5/16"	33 1/8"	78 3/8"	220 V Tri Phase	20 A	4.2 Kw